JESMAY











4-Wire 7" AHD **Video Door Phone**























MODEL: M4732



4-Wire 7" AHD **Video Door Phone**

INSTALLATION DIAGRAM



FEATURES

- 1080P 7" video door phone with touch screen.
- RFID card entry.
- · Picture in picture.
- The outdoor panel can supply power to the electronic lock.
- · Motion detection function.
- · Automatic snapshot or video recording with the call.
- Up to 2 outdoor panels+4 indoor monitors+2 CCTV cameras.
- · Album.
- · Customize ringtone.
- · Indoor monitor unlock & outdoor panel unlock.
- Door-call transfers to other monitors.
- · Internal call between monitors.
- · 4-wire connection between outdoor panel and monitor.

SPECIFICATIONS

| Monitor | |
|-----------------------|--------------------------------------|
| Monitor screen | 7" touch TFT LCD |
| Resolution | 1024(H) X 600(V) |
| Signal supports | 1080P/720P/CVBS/CVI/TVI |
| Conversation mode | Hands-free half-duplex communication |
| Conversation duration | 120s |
| SD card | Support 256G max. |
| Power consumption | 11W Max. |
| Power supply | DC 12V |
| Working temperature | -10°C~+60°C |
| Installation method | Surface mount |

177.9

| | ' ' | |
|-------------------------------------|---|--|
| Outdoor Panel | | |
| Image sensor | 1/3 inch wide angle CMOS camera | |
| IR-CUT | YES | |
| RFID card | YES | |
| Definition | 1080P/720P/CVBS | |
| Camera view angle | 115° | |
| LEDs for night | IR LEDs(120°) * 4pcs | |
| Protection degree | IP65 | |
| Supply power to the electronic lock | 20V ~24V(optional, refer to actual model) | |
| Power consumption | 3W Max. | |
| Power supply | DC 12V | |
| Working temperature | -20°C~+50°C | |
| Installation method | Surface mount | |

JESMAY ELECTRONICS COMPANY LIMITED

