

# CATALOG

Network · Digital · HD · Intelligent

Video Door Phone



**LB TechnologyCo., Ltd.**

Add: No. 1 of Fuhua Road, Anfu District, Tanzhou Town,  
Zhongshan City, Guangdong Province, China

<http://www.lbtech.com.cn>

Professional CCTV Manufacturer  
2024 Ver 1.0

## Safe &Secure

Security needs to live up to real-world environments.  
It's also a heartfelt reassurance.  
LBTechthe best in overall security.  
Utilizing innovation to make you feel at ease,  
Let your business be problem-free.



## Introduction

Zhongshan LB Technology CO.,LTD ,founded in 2002, is a high-tech company specializing in R&D, production, and sale of home security consumer electronics. Our strong R&D team combined with a full set of production facilities, from molding to plastic injection, to SMT and final assembly, guarantee our product quality.

For years, LB Technology has researched and developed a series of security products , such as Video door phone, Wifi video door phone, wireless transmission products and wireless monitoring equipment. After many years of R&D, we can now combine our capabilities to offer our customers innovative home security products, including monitoring ,alarm, and protection systems , ranging from IP video door phone, IP cameras to monitor your baby or elderly ,IP home alarms which detect illegal invasion ,fire ,gas leakage, flood etc.

The major of our products are IP-enabled which means that you can be notified promptly or check on your home, 24-hours a day , anywhere in the world .

The company has the honor of “trusted supplier” from our many customers as we believe quality is the life of a company. We have ISO9000 and ISO14001 certifications as well as being recognized as “Top 50 Company in China’ s Security Industry” , “Top 10 Customer satisfaction products” , and “The Golden Censor Prize on National Security Exhibition” . As we have many years of experience exporting to many different countries, the majority of our products are certified CE, ROHS, UL, and FCC.

LB tech will carry forward the spirit of “ constant innovation and pursuit of excellence” under the motto of “ lead the way via technology , win the market through quality” . Our goal is to be your elite partner in supplying CCTV and home consumer electronics to the world.



**LB TechnologyCo., Ltd.**

Add: No.1 of Fuhua Road,Anfu DistrictTanzhouTown,Zhongshan CityGuangdongProvince,China  
<http://www.lbtech.com.cn>





# Qualification honor



# Product Line-Up Contents


## Wifi Video Door Phone

- 01-02  
Super IP Intercom
- 03-06  
IP Intercom
- 07-10  
2-Wired Digital System


## Analog Video Door Phone

- 11-14  
2-Wired Analog System
- 15-18  
4-Wired AHD Monitor
- 19-22  
Standard Definition Monitor
- 23-26  
AHD Doorbell
- 27-28  
Analog Doorbell

Outdoor Bell




Indoor Monitor



# Wifi Video Door Phone









Wifi Video Door Phone

- Support CVI / TVI / IPC / AHD / CVBS video input
- Support 4 analog cameras(2 doorbells & 2 CCTV cameras) or 2 analog cameras & 2 digital cameras(2 doorbells & 2 IPC)
- Up to 4 1080P cameras can be connected with 4 indoor monitors(optional)
- 10 inch TFT display[AHD:1024(H)x768(V)]
- Support video recording/ snapshot


System diagram



LB96361TH4W-CEMP



96360TH2W-CEM



Specifications

Model	LB96361TH4W-CEMP	96360TH2W-CEM
Display	10.1" touch TFT LCD	10" touch TFT LCD
Resolution	1024(H) X 600(V)	1024(H) X 600(V)
Video	AHD/CVI/TVI/CVBS/IPC	AHD/CVBS/CVI/TVI
Unlock	Support mobile phone and tablet to unlock	Support mobile phone and tablet to unlock
Touch key	Yes	Yes
Additional memory	SD card (256GB max.)	SD card (256GB max.)
Intercom mode	Hands-free dual communication	Hands-free dual communication
Conversation duration	120s	120s
WIFI	Yes	Yes
Power consumption	12W Max.	15W Max.
Power supply	Built-in power supply(AC100-240V)	DC12V/2A
Operating temp.	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount

4-Wire Wifi 1080P Video Door Phone




Wifi Video Door Phone


- OSD Menu
  - Support AHD (1080P) 2 doorbell units and AHD (1080P) 2 CCTV cameras at most
  - Support connect with analog external monitor
  - Support monitoring, unlocking, talking
  - Adjustable brightness, contrast, ring volume and speaker volume
- Support motion detect function
  - Choose 8 MP3 ring tone
  - Photo capture & video by mobile phone
  - Support IOS/Android system mobile phone and tablet
  - Simple 4-wire connection



System diagram



4-Wire Wifi 1080P Video Door Phone / 10" Wifi Seires





Specifications



Model	96360NTW-CEM
Display	10" TFT LCD(16:9)
Resolution	1024(H) X 600(V)
Video	PAL/NTSC
Unlock	Support mobile phone and tablet to unlock
Touch key	Yes
Additional memory	Support additional SD card (256GB max.)
System	LINUX
System upgrade	Support upgrade by SD card
Port	10/100M, WIFI (IEEE802.11b/g/n)
Power consumption	18W max.
Wifi	Yes
Power supply	DC12V 1.5A
Operating temp.	-10°C~+60°C
Installation	Surface mount

4-Wire Wifi 1080P Video Door Phone / 7" Wifi Seires

96379NTW-CEM



96319NTW





Touch Screen

Specifications



Model	96319NTW	96379NTW-CEM
Display	7" touch TFT LCD(16:9)	7" touch TFT LCD(16:9)
Resolution	1024(H) X 600(V)	1024(H) X 600(V)
Video	PAL/NTSC	PAL/NTSC
Recording	/	Yes
Unlock	Support mobile phone and tablet to unlock	Support mobile phone and tablet to unlock
Touch key	Yes	Yes
Additional memory	Support additional SD card(256GB max)	Support additional SD card(256GB max)
System	Linux	Linux
System upgrade	Support upgrade by SD card	Support upgrade by APP or IE
Port	10/100M,WIFI(IEEE802.11b/g/n)	10/100M,WIFI(IEEE802.11b/g/n)
Power consumption	15W Max.	15W Max.
WIFI	Yes	Yes
Power supply	DC12V/2A	DC12V
Operating temp.	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount

4-Wire Wifi 1080P Video Door Phone / 7" Wifi Seires



96377 Series



96319 Series




JM96329NW(B)



Specifications

Model	96377NW JM96379NTW	96319NW-CEMP 96319NW-CEMP	JM96329NW(B)
Display	7" touch TFT LCD(16:9)	7" touch TFT LCD(16:9)	7" touch TFT LCD(16:9)
Resolution	1024(H) X 600(V)	1024(H) X 600(V)	1024(H) X 600(V)
Video	PAL/NTSC	PAL/NTSC	PAL/NTSC
Recording	/	Yes	/
Unlock	Support mobile phone and tablet to unlock	Support mobile phone and tablet to unlock	Support mobile phone and tablet to unlock
Touch key	Yes	Yes	Yes
Additional memory	Support additional SD card(256GB max)	Support additional SD card(64GB max)	Support additional SD card(256GB max)
System	Linux	Linux	Linux
System upgrade	Support upgrade by SD card	Support upgrade by APP or IE	Support upgrade by SD card
Port	10/100M,WIFI(IEEE802.11b/g/n)	10/100M,WIFI(IEEE802.11b/g/n)	10/100M,WIFI(IEEE802.11b/g/n)
Power consumption	15W Max.	15W Max.	15W Max.
WIFI	Yes	Yes	Yes
Power supply	DC12V/2A	DC12V	DC12V/2A
Operating temp.	-10°C~+60°C	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount	Surface mount

# 2-Wired 1080P Digital System



## 2-Wired 1080P Digital System



97319TW-CEM

### Features

- 7 inch touch TFT display
- Internal call between indoor units
- Support key-unlock, call transfer, and monitoring function
- Up to 2 digital doorbells can be connected with 2 indoor monitors
- Adjustable brightness, ring volume and speaker volume
- Choose 11 mp3 polyphonic melodies, support custom mp3 ring tone function
- Support TF card recording and upgrate
- Support message function
- Support MD alarm function
- Support multi-language system
- Support photo frame, and playback the photo from TF card
- Support photo capture and video recording




97231CR-CS

### Features

- Wide angle camera
- Anti-oxidation aluminium alloy panel
- Simlpe 2-wire connection
- IR LED illumination for better night vision
- Keypad with white LED backlight for night operation
- With ring indication when button pressed
- Support unlock by ID card, up to 40 unlock cards can be added.




2-Wired 1080P Digital System



Specifications

Model	97319TW-CEM	97368TW-CEM
Display	7" touch TFT LCD	7" touch TFT LCD
Resolution	1024(H) X 600(V)	1024(H) X 600(V)
Video	H.264	H.264
TF card	Support 128G max.	Support 128G max.
Intercome mode	Hands-free dual communication	Hands-free dual communication
Conversation duration	120s	120s
Power consumption	7W Max.	7W Max.
Power supply	DC24V/0.75A	DC24V/0.75A
Operating temp.	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount

2-Wired 1080P Digital System



Specifications


Model	97231CR-H2	Model	97271CR-CS/97701CR-CS/ 97702CR-CS
Image Sensor	1/2.9 inch wide angle COMS camera	Image Sensor	1/2.9 inch wide angle COMS camera
IR-CUT	YES	IR-CUT	YES
ID card	No	ID card	YES
Definition	H.264 1920*1080	Definition	H.264 1920*1080
View angle	126°	View angle	126°
LEDs for night	IR LEDs(120°) * 4pcs	LEDs for night	IR LEDs(120°) * 4pcs
Power consumption	3W Max.	Power consumption	3W Max.
Power supplier	Supplied from indoor unit	Power supplier	Supplied from indoor unit
Operating temp.	-20°C~+50°C	Operating temp.	-20°C~+50°C
Installation	Suface/flush mount	Installation	Suface/flush mount

# 2-Wired Analog System



- 7 inch TFT display
- Internal call between indoor units
- Support key-unlock, call transfer, and monitoring function
- One doorbell can be connected with1 indoor monitors
- Simple 2-wire connection
- Friendly GUI for esay operation
- Support video record and photosnap


# 2-Wired Analog System



## Specifications

Model	92319 / 92329	92337
Display	7" TFT LCD	7" TFT LCD
Resolution	1024(H) X 600(V)	1024(H) X 600(V)
Video	PAL/NTSC	PAL/NTSC
Memory	Support additonal TF card(32GB Max.)	NO
Conversation duration	120s	120s
Power consumption	6W Max.	6W Max.
Power supply	24V /0.75A	24V /0.75A
Operating temp.	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount


2-Wired Analog System



Specifications

Model	92231CR-CMS / 92243CR-CMS / 92221CR-CMS
Camera sensor	1/4 inch pinhole CMOS camera
View angle	100°
Definition	1000TVL
LEDs for night	IR LEDs (120°)
IR-CUT	YES
Power consumption	3W Max.
Power supply	Supplied from indoor unit
Operating temp.	-20°C~+60°C
Installation	Surface/Flush mount


2-Wired Analog System



Specifications


Model	92701CR-CS / 92702CR-CS
Camera sensor	1/4 inch pinhole CMOS camera
View angle	100°
Definition	1000TVL
LEDs for night	IR LEDs (120°)
IR-CUT	YES
ID Card	Support 1pc management card and 248pcs user cards
Power consumption	3W Max.
Power supply	Supplied from indoor unit
Operating temp.	-20°C~+60°C
Installation	Surface/Flush mount





AHD Video Door Phone


- Support AHD 1080P\720P\CVBs input
- Support OSD menu
- Support motion detect function
- Support choose MP3 ring tone
- Support photo frame
- Adjustable brightness, contrast, ring volume and speaker volume
- Internal call between indoor units
- Support key-unlock, call transfer, and monitoring function
- Up to 2 doorbells and 2 CCTV cameras(AHD or standard definition)
- Support photo capture and video recording



Specifications


Model	94360H2T	94352H2-CEMP
Display	10.1" touch TFT LCD	10".1 TFT LCD
Resolution	1024(H) X 600(V)	1024(H) X 600(V)
Video	1080P/720P/CVBS/TVI/CVI	1080P/720P/CVBS/TVI/CVI
Intercom mode	Hands-free dual communication	Hands-free dual communication
Conversation duration	120s	120s
OSD menu	Yes	Yes
Touch key	Yes	Yes
Memory	Support additional TF card (128G max.)	Support additional TF card(128GB max.)
Motion detect	Yes	Yes
Power consumption	3W Max.	3W Max.
Power supply	DC12V/1A	Built-in(AC100~240V)
Operating temp.	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount





Specifications

Model	94377H2 / M94329H2	94379H2T
Display	7" TFT LCD	7" thouch TFT LCD
Resolution	1024(H) X 600(V)	1024(H) X 600(V)
Video	1080P/720P/CVBS/TVI/CVI	1080P/720P/CVBS/TVI/CVI
Intercome mode	Hands-free dual communication	Hands-free dual communication
Conversation duration	120s	120s
OSD menu	Yes	Yes
Touch key	Yes	Yes
Memorty	Support additional TF card (64G max.)	Support additional TF card(128GB max.)
Motion detect	Yes	/
Power consumption	≥10W	7W Max.
Power supply	DC12V/1A	DC12V/1A
Operating temp.	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount



Specifications

Model	94319H2-P	94319H2-CEMP	94329H2-CEMP
Display	7" TFT LCD	7" TFT LCD	7" TFT LCD
Resolution	1024(H) X600(V)	1024(H) X 600(V)	1024(H) X600(V)
Video	1080P/720P/CVBS/TVI/CVI	1080P/720P/CVBS/TVI/CVI	1080P/720P/CVBS/TVI/CVI
Intercome mode	Hands-free dual communication	Hands-free dual communication	Hands-free dual communication
Conversation duration	120s	120s	120s
OSD menu	Yes	Yes	Yes
Touch key	Yes	Yes	Yes
Memorty	Support additional TF card (128G max.)	Support additional TF card(128GB max.)	Support additional TF card(128GB max.)
Power consumption	8W Max.	8W Max.	8W Max.
Power supply	Built-in(AC100~240V)	Built-in power supply(AC100~240V)	Built-in power supply(AC100~240V)
Operating temp.	-10°C~+60°C	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount	Surface mount


Standard Definition Monitor



Video Door Phone

- Hands-free video intercom
- Internal call between indoor units
- Support key-unlock, call transfer, and monitoring function
- Up to 2 doorbells can be connected with 4 indoor monitors (backward compatible)
- Support one channel camera surveillance
- Adjustable brightness, contrast, ring volume and microphone volume
- Choose 16 polyphonic melodies


7" Classic Series



Specifications

Model	94329A-CEMP	94339A-CEMP	94358-CE 94358-CEP
Display	7" TFT LCD	7" TFT LCD	7" TFT LCD
Resolution	1024(H) X 600(V)	800(H) X 481(V)	800(H) X 480(V)
Video	PAL/NTSC	PAL/NTSC	PAL/NTSC
Intercome mode	Hands-free dual communication	Hands-free dual communication	Hands-free dual communication
Conversation duration	120s	120s	120s
OSD menu	Yes	/	/
Touch key	Yes	Yes	/
Memory	Support additional TF card (32G max.)	Support additional TF card(32GB max.)	/
Power consumption	6W Max.	6W Max.	6W Max.
Power supply	Built-in power supply(AC100~240V)	Built-in power supply(AC100~240V)	12V1A
Operating temp.	-10°C~+60°C	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount	Surface mount


7" Classic Series



Specifications

Model	94328-CEMP	94347-CE 94347-CEP	94337-CE 94337-CEP	94329-CE 94329-CEP
Display	7" TFT LCD	7" TFT LCD	7" TFT LCD	7" TFT LCD
Resolution	800(H) X 480(V)	1024(H) X 600(V)	800(H) X 481(V)	1024(H) X 768(V)
Video	PAL/NTSC	PAL/NTSC	PAL/NTSC	1080P/720P/CVBS/TVI/CVI
Intercome mode	Hands-free dual communication			
Conversation duration	120s	120s	120s	120s
Power consumption	8W Max.	8W Max.	8W Max.	8W Max.
Power supply	Built-in(AC100~240V)	Built-in(AC100~240V)	DC12V/2A	DC12V/2A
Operating temp.	-10°C~+60°C	-10°C~+60°C	-10°C~+60°C	-10°C~+60°C
Installation	Surface mount	Surface mount	Surface mount	Surface mount

4" Classic Series



Specifications

Model	JM94345-CE(B)
Display	4.3" TFT LCD
Resolution	320(H) X 240(V)
Video	PAL/NTSC
Intercome mode	Hands-free dual communication
Conversation duration	120s
Memorty	No
Motion detect	No
Power consumption	5W Max.
Power supply	DC12V/2A
Operating temp.	-10°C~+60°C
Installation	Surface mount



AHD Out doorbell



Features:

- Support 1080P/720P and CVBS resolution
- Support IR-CUT
- Press button to switch the output mode between AHD / CVBS
- Wide angle camera
- Anti-oxidation aluminium alloy panel
- Simlpe 4-wire connection
- IR LED illumination for better night vision
- Keypad with blue LED backlight for night operation
- With ring indication when button pressed

AHD 1080P Out Doorbell




Specifications

Model	LB94231R-H2(CE) 94231R-H2	94232CR-H2 LB94232CR-H2 LB94232CR-H2(CE)	94231R-CS	94225-H2
Camera sensor	1/3 inch CMOS camera	1/3 inch CMOS camera	1/3 inch CMOS camera	1/3 inch CMOS camera
Definition	1080P/720P/CVBS	1080P/720P/CVBS	1080P/720P/CVBS	1080P/720P/CVBS
Unlock mode	/	/	ID card unlock	password / ID card unlock
View angle	120°	120°	120°	120°
LEDs for night	IR LEDs(120°)	IR LEDs(120°)	IR LEDs(120°)	IR LEDs (120°)
ID card	/	/	Support 1pc management card and 248pcs user cards	Support 1pc management card and 248pcs user cards
IR-CUT	Yes	Yes	Yes	Yes
Power consumption	3W Max.	3W Max.	3.5W Max.	3W Max.
Power supply	Supplied from indoor	Supplied from indoor	External switching power supply DC 12V	External switching power supply DC 12V
Operating temp.	-10°C~+60°C	-10°C~+60°C	-10°C~+60°C	-10°C~+60°C
Installation	Surface or embedded mount	Surface or embedded mount	Surface mount	Surface mount



AHD 1080P Out Doorbell



Specifications

Model	94243CR-H2
Camera sensor	1/3 inch CMOS camera
View angle	120°
Definition	1080P/720P/CVBS
LEDs for night	IR LEDs (120°)
Touch button	YES
ID card	No
IR-CUT	YES
Power consumption	3W Max.
Power supply	Supplied from indoor unit
Operating temp.	-20°C~+60°C
Installation	Surface mount

Model	94701CR-CS / 94702CR-CS
Camera sensor	1/4 inch pinhole CMOS camera
View angle	100°
Definition	1000TVL
LEDs for night	IR LEDs (120°)
IR-CUT	YES
ID Card	Support 1pc management card and 248pcs user cards
Power consumption	3W Max.
Power supply	Supplied from indoor unit
Operating temp.	-20°C~+60°C
Installation	Surface/Flush mount

AHD 1080P Out Doorbell



Specifications


Model	94271CR-H2	94272CR-H2	94224R-H2
Camera sensor	1/3 inch CMOS camera	1/3 inch CMOS camera	1/3 inch CMOS camera
View angle	120°	120°	105°
Definition	1080P/720P/CVBS	1080P/720P/CVBS	1080P/720P/CVBS
LEDs for night	IR LEDs (120°)	IR LEDs (120°)	IR LEDs (120°)
Name laber	YES	YES	YES
IR-CUT	YES	YES	YES
Power consumption	3W Max.	3W Max.	3W Max.
Power supply	Supplied from indoor unit	Supplied from indoor unit	Supplied from indoor unit
Operating temp.	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C
Installation	Surface mount	Surface mount	Surface mount




Video Door Phone

- Pinhole /wide angle camera
- Anti-oxidation aluminium alloy panel
- Simple 4-wire connection
- IR LED illumination for better night vision
- With ring indication when button pressed
- Rainproof, Dustproof, and Anti-vandal

94221-CMS



LB94232BR-CMS



Specifications

Model	94221-CMS	LB94232BR-CMS
Camera sensor	1/3inch pinhole CMOS camera	1/4 inch CMOS camera
View angle	65°	85°
Definition	1000TVL	420TVL
LEDs for night	IR LEDs (120°)	IR LEDs (120°)
IR-CUT	YES	/
Power consumption	3W Max.	2W Max.
Power supply	Supplied from indoor unit	Supplied from indoor unit
Operating temp.	-20°C~+60°C	-20°C~+60°C
Installation	Surface mount	Surface mount